

Genset Ratings

Engine Type	Cyl. & Config.	Net flywheel power (kW acc. To ISO 3046)						Bore / Stroke mm	Displ. (l)	Dimensions						Weight ⁴	
		50 Hz/1500 rpm			60 Hz/ 1800 rpm					Length		Width		Height			
		COP ¹	PRP ²	LTP ³	COP ¹	PRP ²	LTP ³			mm	in	mm	in	mm	in	kg	lb

Diesel Engines

D2008L3	3 IL	9.3	9.7	10.2	11.7	12.3	12.9	76/86	1.17	538	21.2	480	18.9	585	23.0	155	342.0
D2008L4	4 IL	13.2	13.8	14.5	16.5	17.2	18.1	76/86	1.56	627	24.7	480	18.9	585	23.0	189	417.0
D2009L3	3 IL	14.7	15.4	16.2	17.0	17.8	18.4	90/90	1.72	597	23.5	490	19.3	612	24.1	180	397.0
D2009L4	4 IL	18.7	19.7	20.6	23.5	24.7	25.9	90/90	2.29	680	26.7	490	19.3	612	24.1	205	452.0
TD2009L4	4 IL	25.6	26.9	28.2	32.1	33.7	35.3	90/90	2.29	680	26.7	522	20.5	633	24.9	210	463.0
F2L2011	2 IL	11.4	12.0	12.6	13.6	14.3	15.1	94 / 112	1.55	645	25.2	588	22.9	707	27.6	212	467.0
F3L2011	3 IL	18.1	19.0	20.0	21.4	22.6	23.8	94 / 112	2.33	756	29.5	588	22.9	701	27.3	254	560.0
F4L2011	4 IL	26.2	27.6	29.0	31.1	32.8	34.5	94 / 112	3.11	868	33.9	588	22.9	722	28.4	293	646.0
BF4L2011	4 IL	34.6	36.4	38.2	41.0	43.2	45.5	94 / 112	3.11	778	30.3	531	20.7	704	27.5	295	650.0
F2M2011	2 IL	11.8	12.4	13.0	14.3	15.0	15.8	94 / 112	1.55	845	33.0	643	25.1	762	29.7	206	454.0
F3M2011	3 IL	18.6	19.4	20.4	22.1	23.3	24.5	94 / 112	2.33	956	37.3	616	24.0	761	29.7	247	545.0
F4M2011	4 IL	26.6	28.0	29.4	31.8	33.5	35.2	94 / 112	3.11	1067	41.6	616	24.0	778	30.3	285	628.0
BF4M2011	4 IL	35.6	37.4	39.2	42.8	45.0	47.3	94 / 112	3.11	1080	42.1	649	25.3	787	30.7	286	631.0
F3L914	3 IL	27.0	28.0	29.0	32.0	33.0	35.0	102 / 134	3.06	670	26.4	704	27.7	795	31.3	351	774.0
F4L914	4 IL	36.0	37.0	39.0	42.0	44.0	47.0	102 / 134	3.21	777	30.6	704	27.7	796	31.3	402	886.4
F6L914	6 IL	54.0	56.0	59.0	64.0	67.0	79.0	102 / 134	4.31	1057	41.6	704	27.7	806	31.7	541	1192.9
BF6L914C G1	6 IL	80.0	84.0	88.0	98.0	103.0	108.0	102 / 134	6.47	1125	44.3	726	28.6	919	36.2	585	1289.9
BF6L914C G2	6 IL	107.0	113.0	119.0	129.0	137.0	114.0	102 / 134	6.47	1387	54.6	739	29.1	992	39.1	610	1345.1
BF4M2012	4 IL	51.0	54.0	60.0	60.0	63.0	70.0	101 / 126	4.04	1092.5	43.0	602	23.7	951	37.4	444	0.0
BF4M2012C	4 IL	64.0	70.0	74.9	75.0	79.0	88.0	101 / 126	4.04	1182.8	46.6	733	28.8	971	38.2	466	0.0
BF4M1013EC	4 IL	88.0	93.0	98.0	100.0	105.0	110.0	108 / 130	4.76	1318	51.9	739	29.1	1001	39.4	570	1256.9
BF4M1013FC	4 IL	96.0	101.0	106.0	111.0	116.0	122.0	108 / 130	4.76	1320	52.0	728.5	28.7	1151.5	45.3	570	1256.9
BF6M1013EC	6 IL	135.0	142.0	149.0	148.0	155.0	163.0	108 / 130	7.15	1602	63.1	866	34.1	1140	44.9	735	1620.7
BF6M1013FC G1	6 IL	154.0	162.0	170.0	179.0	188.0	197.0	108 / 130	7.15	1602	63.1	866	34.1	1140	44.9	735	1620.7
BF6M1013FC G2	6 IL	-	166.0	183.0	-	186.0	204.0	109 / 130	7.15	1607.3	63.3	1003	39.5	1440.3	56.7	802	1768.4
BF6M1013FC G3	6 IL	170.0	179.0	188.0	188.0	207.0	224.9	108 / 130	7.15	1607.3	63.3	1003	39.5	1440.3	56.7	802	1768.4
BF6M1015C	6 IL	250.0	285.0	345.0	271.0	310.0	341.0	132 / 145	11.90	976	38.4	932	36.7	1172	46.1	920	2028.6
BF6M1015CP	6 IL	303.0	338.0	365.0	320.0	351.0	384.0	132 / 145	11.90	976	38.4	932	36.7	1172	46.1	920	2028.6
BF8M1015C	V 8	333.0	380.0	459.0	362.0	413.0	454.0	132 / 145	15.90	1190	46.9	940	37.0	1172	46.1	1120	2469.6
BF8M1015CP	V 8	399.0	448.0	490.0	426.0	473.0	517.0	132 / 145	15.90	1190	46.9	940	37.0	1172	46.1	1120	2469.6